


1600 Series



Misurare													Carico nominale (N)	Peso (kg)
Selezionare Inchiesta NO.			D		D		B				Smussatura		Cr	
			mm	pollice	mm	pollice	Tipo aperto		Tipo schermato		rsmin (r)			
							mm	pollice	mm	pollice	mm	pollice		
1601	4.762	0.1875	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.007	
1602	6.35	0.25	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.0065	
1603	7.938	0.3125	22.225	0.875	7.144	0.2813	8.731	0.3437	0.3	0.012	3290	1360	0.012	
1604	9.525	0.375	22.225	0.875	7.144	0.2813	8.731	0.3437	0.4	0.016	3330	1410	0.0105	
1605	7.938	0.3125	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.3	0.012	3330	1410	0.016	
1606	9.525	0.375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	3330	1410	0.015	
1607	11.112	0.4375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	2690	1270	0.015	
1614	9.525	0.375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.03	
1615	11.112	0.4375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.028	
1616	12.7	0.5	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.026	
1620	11.112	0.4375	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.05	
1621	12.7	0.5	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.048	
1622	14.288	0.5625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.046	
1623	15.875	0.625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.041	
1628	15.875	0.625	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.072	
1630	19.05	0.75	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.069	
1633	15.875	0.625	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.092	
1635	19.05	0.75	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.24	9390	5020	0.09	
1638	19.05	0.75	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.145	
1640	22.225	0.875	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.133	
1641	25.4	1	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.121	
1652	28.575	1.125	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.211	
1654	31.75	1.25	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.193	
1657	31.75	1.25	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.232	
1658	33.337	1.3125	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.21	