


Starter Bearing



Selezionare	Inchiesta	Cuscinetto n	Dimensioni del confine (mm)				Indice di carico di base(N)		Limite di velocità giri al minuto	Peso Kg	Tipo
			D	D	B	r min	Cr	Cor			
608-2RDA	8	22	7	0.30	3350	1400	32000	0.02	A		
B800-2RDA	8	23	24	0.30	3300	1370	34000	0.03	B		
B874-2RDA	8	22	11	0.30	3300	1370	34000	0.03	C		
B879-2RDA	8	23	11	0.30	3300	1370	34000	0.03	C		
B885-2RDA	8	23	14	0.30	3300	1370	34000	0.03	C		
629-2RDA	9	26	8	0.30	4550	1960	30000	0.02	A		
6000-2RDA	10	26	8	0.30	4550	1960	29000	0.02	A		
62000-2RDA	10	26	10	0.30	4550	1960	26000	0.02	A		
6200-2RDA	10	30	9	0.60	5100	2390	25000	0.04	A		
B1046-2RDA	10	23	11	0.30	2700	1270	32000	0.02	C		
B1050-2RDA	10	27	11	0.30	4570	1970	30000	0.03	C		
B900-2RDA	10	27	14	0.30	4570	1970	30000	0.03	B		
6001-2RDA	12	28	8	0.30	5100	2390	26000	0.02	A		
6201-2RDA	12	32	10	0.60	6100	2750	22000	0.04	A		
62201-2RDA	12	32	14	0.60	6100	2750	22000	0.05	A		
6301-2RDA	12	37	12	1	9700	4200	20000	0.06	A		
B2011-2RDA	12	35	18	0.60	6106	2770	22000	0.07	A		
B2012-2RDA	12	32	10	0.60	6820	3060	22000	0.04	C		
R8-2RDA*	12.70	28.58	7.94	0.40	4040	1750	19000	0.02	A		
6002-2RDA	15	32	9	0.30	5600	2840	22000	0.03	A		
6202-2RDA	15	35	11	0.60	7750	3600	19000	0.05	A		

Starter Bearing

6302-2RDA	15	42	13	1	11400	5450	17000	0.09	A
B1583-2RDA	15	47	18	0.30	13460	6485	17000	0.14	A
B2021-2RDA	15	35	13	0.60	7750	3600	19000	0.05	A
B2022-2RDA	15	38	19	0.60	7750	3600	19000	0.08	A
B3021-2RDA	15	43	13	1	11400	5450	17000	0.08	A
B3022-2RDA	15	46	14	1	13500	6550	16000	0.10	A
B3031-2RDA	15	47	14	1	13500	6550	16000	0.11	A
B3041-2RDA	15	52	16	1.10	16000	7938	14000	0.15	A
6003-2RDA	17	35	10	0.30	6800	3350	20000	0.04	A